

# WHEEL SPECIFICATIONS

All wheel sizes come in Machined, Polished and Eco Shield (ES3) finishes.

Further sizes are available upon request.

**Nuts, donut rings and nut cap covers are available from stock.**



No. of Bolt Holes	Bolt Hole Diameter (mm)	PCD (mm)	Centre Hole Diameter (mm)	Disc Thickness (mm)	Offset/HDS (mm)	Load Rating (kg)	Weight (kg)
<b>6.00 x 17.5</b>							
6	24/30	245	191	19	133 HDS	2000kg	12.9
6	26	245	202	19	133 HDS	2000kg	13.2
6	26	205	161	19	133 HDS	2000kg	13.2
10	26	225	176	19	135 HDS	2000kg	12.5
<b>6.75 x 17.5</b>							
6	26	245	202	20	140 HDS	2500kg	13.9
8	24/30	275	221	20	140 HDS	2500kg	13.5
10	26	225	175	20	141 HDS	2500kg	13.9
<b>7.50 x 19.5</b>							
8	26/30	275	221	20	155 HDS	2900kg	18
10	26/32	225	176	20	155 HDS	2900kg	18
<b>7.50 x 22.5</b>							
10	26/32	335	281	24	159 HDS	3750kg	24
<b>8.25 x 22.5</b>							
10	26/32	335	281	28	170 HDS	3750kg	25.2
<b>9.00 x 22.5</b>							
10	26/32	335	281	24	175 HDS	4125kg	26.1
<b>11.75 x 22.5 ET0</b>							
10	26/32	335	281	24	ET0	5000kg	24.9
<b>11.75 x 22.5 ET120</b>							
10	26/32	335	281	25.6	ET120	5000kg	27
<b>11.75 x 22.5 ET135</b>							
10	26/32	335	281	25.6	ET135	5000kg	27