

TIA WHEELS

STEEL WHEEL CATALOGUE

THE COMPLETE SIZE GUIDE

Explore our comprehensive range of steel wheel sizes and specifications to find the perfect fit for your business needs.

WHO WE ARE

ABOUT US



Our story began in 2012. Since then, our unwavering commitment to quality and innovation has propelled TIA Wheels beyond our origins as wholesalers to trusted commercial industry leaders.

Today, we stand as trusted OEM-approved distributors of our very own TIA Wheels brand. With a diverse range of alloy and steel wheels, we supply everything from individual components to full assemblies for all your commercial and industrial requirements.

But our mission goes beyond providing exceptional products. We're here to offer expertise, personalised support, and a seamless experience, every step of the way.

We're your partner in wheels, from production to distribution.

01 | About TIA Wheels

Who We Are	1
Our Steel Wheels	2

02 | Wheel Specifications

17.5'' Steel Wheels	3
19.5'' Steel Wheels	14
22.5'' Steel Wheels	22

03 | About TIA Group

Who We Are	61
Our Divisions	62

MEET TIA'S STEEL WHEELS

STEEL WHEELS



Combining durability with reliability, our steel wheels provide lasting support for heavy-duty applications on the road even in the most demanding conditions.

Now available in two distinct finishes, Classic and Premium, TIA's steel wheel range gives customers more choice than ever before, with options to suit every budget, aesthetic and application.

Our premium alternative features a triple-layer powder-coated finish that not only enhances visual appeal but dramatically increases resistance to corrosion, withstanding 1,200 hours of salt spray testing, making them TIA's most robust steel wheels to date.



CLASSIC STEEL

Our classic wet-paint finish is a durable matt option that delivers reliable protection.



PREMIUM STEEL

Shiny, powder-coated prestige. Enhance your looks with this OE-grade finish.

17.5 x 6.00
STEEL WHEELS

Reccomended tyre size(s): 8R17.5 | 8.5R17.5 | 9.5R17.5 | 205/65R7.5 | 205/75R17.5 | 215/75R17.5 | 225/75R17.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1701	5	10	22.19	203.2	5-ø29	146	SR22	135	1700
BW1701A	5	10	22.19	203.2	5-ø29	146	SR22	118	1700
BW1701B	6	12	23.77	203.2	5-ø29	146	SR22	127	1700
BW1701C	5	10	22.19	203.2	5-ø29	146	SR22	128	1700
BW1701E-JL	5	10	22.19	203.2	5-ø29	146	SR22	122	1700
BW1702	6	12	24.94	205	6-ø21	161	1x45°	127	1700
BW1702A	5	10	21.15	205	6-ø21	161	1x45°	125	1700
BW1702B	5	10	20.75	205	6-ø21	161	SR18	118	1700
BW1702C	5	10	20.75	205	6-ø21	161	SR18	124	1700
BW1702D	5	10	20.75	205	6-ø21	161	SR18	127	1700
BW1702E-ZT	5	10	21.15	205	6-ø21	161	1x45°	118	1700
BW1702F	6	12	24.94	205	6-ø21	161	1x45°	118	1700
BW1702G	5	10	20.75	205	6-ø21	161	SR16	124	1700
BW1702H	5	10	20.75	205	6-ø21	161	SR16	133	1700
BW1702I	6	12	24.94	205	6-ø21	161	SR18	127	1700

17.5 x 6.00
STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1702J-DF	5	11	22	205	6-ø21	161	1x45°	126	1700
BW1702K-DF	5	11	22	205	6-ø21	161	1x45°	125	1700
BW1703	6	12	24.54	205	6-ø21	161	90°	125	1700
BW1703A	5	10	20.8	205	6-ø21	161	90°	125	1700
BW1704	6	12	25.34	208	5-ø32	150	SR22	127	1700
BW1705	6	12	24.68	222.25	6-ø32	164	SR22	135	1700
BW1705A	5	10	21.64	222.25	6-ø32	164	SR22	135	1700
BW1705B-DF	5	11	22.6	222.25	6-ø32	164	SR22	127	1700
BW1705C	6	12	24.45	222.25	6-ø32	164	SR22	127	1700
BW1705D	5	10	21.43	222.25	6-ø32	164	SR22	127	1700
BW1705E	5	10	21.13	222.25	6-ø32	164	SR22	118	1700
BW1705E-ZT	5	10	21.13	222.25	6-ø32	164	SR22	118	1700
BW1705F	5	10	21.43	222.25	6-ø32	164	SR22	125	1700
BW1705H	6	12	23.24	222.25	6-ø32	164	SR22	128	1700
BW1705J	5	10	21.13	222.25	6-ø32	164	SR22	115	1700
BW1705K	6	10	23.2	222.25	6-ø32	164	SR22	122	1700

17.5 x 6.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1705L	6	10	23.2	222.25	6-ø32	164	SR22	127	1700
BW1705M	5	12	22.6	222.25	6-ø32	164	SR22	127	1700
BW1705P	5	12	22.6	222.25	6-ø32	164	SR22	135	1700
BW1706	6	12	24.33	225	6-ø33	164	90°	125	1700
BW1707	6	12	24.56	225	10-ø26	176	1x45°	125	1700
BW1707B	6	12	24.77	225	10-ø26	176	1x45°	135	1700
BW1707C	6	12	24.47	225	10-ø26	176	1x45°	123	1700
BW1707D	5	10	20.8	225	10-ø26	176	1x45°	125	1700
BW1707E	5	10	20.8	225	10-ø26	176	1x45°	135	1700
BW1707F	6	12	24.56	225	10-ø26	176	1x45°	117	1700
BW1707G	5	10	20.8	225	10-ø26	176	SR18	135	1700
BW1707H	6	12	24.56	225	10-ø26	176	SR18	125	1700
BW1707K	6	12	24.56	225	10-ø26	176	1x45°	130	1700
BW1708	6	12	23.52	203.2	5-ø29	146	SR22	118	1700
BW1708A	6	12	23.52	203.2	5-ø29	146	SR22	120	1700
BW1709	6	12	25.1	208	5-ø32	150	SR22	118	1700

17.5 x 6.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1709B	5	10	21.28	208	5-ø32	150	SR22	120	1700
BW1709C	5	10	21.28	208	5-ø32	150	SR22	127	1700
BW1709D	6	12	25.1	208	5-ø32	150	SR22	135	1700
BW1709E	5	10	21.28	208	5-ø32	150	SR22	135	1700
BW1709F	6	12	-	208	5-ø32	150	SR22	118	1700
BW1716	5	11	22.14	205	6-ø21	160	1x45°	127	1700
BW1717	5	10	21.26	203.2	5-ø32	146	SR22	118	1700
BW1717A	5	10	21.48	203.2	5-ø32	146	SR22	127	1700
BW1717B	5	10	21.68	203.2	5-ø32	146	SR22	135	1700
BW1717C	6	12	25.5	203.2	5-ø32	146	SR22	130	1700
BW1717D	6	12	25.5	203.2	5-ø32	146	SR22	118	1700
BW1719A	6	12	24.56	225	10-ø27	176	SR18	133	1700
BW1721	5	10	-	222.25	6-ø24	161	1x45°	127	1700
BW1722A	5	10	-	275	8-ø26	221	SR18	134	1700
BW1722B	6	12	-	275	8-ø26	221	SR18	134	1700
BW1722D	6	12	-	275	8-ø26	221	1x45°	135	1700

17.5 x 6.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1730	6	10	23.07	203.2	5-ø32	146	SR22	118	1700
BW1731	6	12	24.68	222.25	6-ø32	164	SR22	135	1700
BW1731A	5	10	20.6	222.25	6-ø32	164	SR22	135	1700
BW1732	6	10	23.09	208	5-ø32	150	SR22	118	1700
BW1732A	5	10	20.95	208	5-ø32	150	SR22	118	1700
BW1733	6	10	-	203.2	5-ø32	146	SR22	118	1700
BW1733A	5	10	-	203.2	5-ø32	146	SR22	118	1700
BW1734	6	10	-	208	5-ø32	150	SR22	118	1700
BW1735	6	12	-	222.25	6-ø32	164	SR22	135	1700
BW1741	6	12	26	275	8-ø24	221	1x45°	135	1700
BW1741A	6	12	26	275	8-ø24	221	SR16	135	1700
BW1749-DF	5	12	-	222.25	6-ø32	165	SR22	126	1700
BW1749A-DF	5	12	-	222.25	6-ø32	165	SR22	129	1700
BW1749B-DF	5	12	-	222.25	6-ø32	165	SR22	133.5	1700
BW1757A	5	10	-	245	6-ø21.5	202	SR16	126	1700
BW1757B	5	10	-	245	6-ø21.5	202	1x45°	126	1700

17.5 x 6.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1759A-ZT	5	10	-	222.25	6-ø24	164	1x45°	127	1700
BW1762	5	8	17.24	170	6-ø17	134	one side SR14	32	-
BW1780-JL	5	10	-	203.2	5-ø24	146	1x45°	122	1700
BW1783-DF	5	11	-	222.25	6-ø26	161	1x45°	125	1700
BW1783A-DF	5	11	-	222.25	6-ø26	161	1x45°	115	1700
BW1785	6	12	24.7	205	6-ø21	160.2	1x45°	127	1700

17.5 x 6.75
STEEL WHEELS

Reccomended tyre size(s): 8R17.5 | 8.5R17.5 | 9.5R17.5 | 10R17.5 | 205/65R17.5 | 205/75R7.5 | 215/75R17.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1710	6	12	24.98	203.2	5-ø29	146	SR22	127	2000
BW1710A	5	10	23	203.2	5-ø29	146	SR22	142	2000
BW1711	6	12	26.4	205	6-ø21	161	1x45°	127	2000
BW1711A	6	12	26.4	205	6-ø21	161	1x45°	138	2000
BW1711B	5	10	22	205	6-ø21	161	1x45°	127	2000
BW1711D	6	12	26.4	205	6-ø21	161	SR16	132	2000
BW1711E	6	10	24.42	205	6-ø21	161	one side SR16	132	2000
BW1711F	5	10	22	205	6-ø21	161	1x45°	138	2000
BW1711G	6	10	24.42	205	6-ø21	161	1x45°	138	2000
BW1712	6	12	26	205	6-ø21	161	90°	127	2000
BW1713	6	12	26.8	208	5-ø32	150	SR22	127	2000
BW1713A	5	10	22.35	208	5-ø32	150	SR22	127	2000
BW1714	6	12	26.14	222.25	6-ø32	164	SR22	127	2000
BW1714A	6	12	26.14	222.25	6-ø32	164	SR22	140	2000
BW1714B	6	12	26.14	222.25	6-ø32	164	SR22	131	2000

17.5 x 6.75
STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1714C	6	12	26.14	222.25	6-ø32	164	SR22	137	2000
BW1714D	5	10	22.5	222.25	6-ø32	164	SR22	137	2000
BW1714E	5	10	22.5	222.25	6-ø32	164	SR22	127	2000
BW1714F	6	10	24.9	222.25	6-ø32	164	SR22	137	2000
BW1714H	5	12	23.7	222.25	6-ø32	164	SR22	137	2000
BW1714I	6	14	28	222.25	6-ø32	164	SR22	138	2000
BW1714J	5	10	22.5	222.25	6-ø32	164	SR22	142	2000
BW1714K-JL	5	10	22.5	222.25	6-ø32	164	SR22	131	2000
BW1714L	6	10	24.9	222.25	6-ø32	164	SR22	141	2000
BW1714M	6	12	26.14	222.25	6-ø32	164	SR22	145	2000
BW1715	6	12	26.23	225	10-ø26	176	1x45°	142	2000
BW1715A	6	12	26.09	225	10-ø26	176	1x45°	153	2000
BW1715B	6	14	28.1	225	10-ø26	176	1x45°	145	2000
BW1715C	5	10	22	225	10-ø26	176	1x45°	142	2000
BW1715E	6	12	26.23	225	10-ø26	176	1x45°	135	2000
BW1715F	5	10	22	225	10-ø26	176	1x45°	145	2000

17.5 x 6.75
STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1715G	5	10	22	225	10-ø26	176	1x45°	135	2000
BW1715H	6	12	26.23	225	10-ø26	176	SR18	142	2000
BW1715I	6	12	26.23	225	10-ø26	176	SR18	135	2000
BW1715J	6	12	26.23	225	10-ø26	176	SR18	130	2000
BW1715K	6	12	26.23	225	10-ø26	176	SR18	145	2000
BW1715L	6	12	26.23	225	10-ø26	176	1x45°	127	2000
BW1715M	5	10	22	225	10-ø26	176	SR18	145	2000
BW1715N	6	12	26.23	225	10-ø26	176	1x45°	145	2000
BW1715P	6	12	26.23	225	10-ø26	176	1x45°	138	2000
BW1715Q	6	14	28.1	225	10-ø26	176	one side SR18	140	2000
BW1715R	6	14	28.1	225	10-ø26	176	one side SR18	135	2000
BW1715S	5	12	23.9	225	10-ø26	176	1x45°	145	2000
BW1715T	5	10	22	225	10-ø26	176	SR18	130	2000
BW1715U	6	10	24.3	225	10-ø26	176	1x45°	142	2000
BW1715V	6	10	24.3	225	10-ø26	176	SR18	142	2000
BW1715W	5	12	23.9	225	10-ø26	176	1x45°	135	2000

17.5 x 6.75
STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1723	6	12	-	275	8-ø21.5	221	SR16	132	2000
BW1723A	6	10	-	275	8-ø21.5	221	SR16	132	2000
BW1723A-01	6	10	-	275	8-ø21.5	221	one side SR16	132	2000
BW1727	6	12	28	275	8-ø26	221	1x45°	143	2000
BW1727A	6	12	27	275	8-ø26	221	1x45°	140	2000
BW1727B	5	10	23.5	275	8-ø26	221	1x45°	140	2000
BW1727C-DRAGON DREAM	6	12	27	275	8-ø26	221	1x45°	142	2000
BW1727F	6	10	25.8	275	8-ø26	221	1x45°	142	2000
BW1737	6	12	27	275	8-ø27	221	SR18	138	2000
BW1737A	6	12	27	275	8-ø26	221	SR18	142	2000
BW1742	5	10	-	225	10-ø27	176	SR18	150	2000
BW1744A	5	10	22.9	275	8-ø24	221	1x45°	140	2000
BW1747-HAEMMERLING	6	12	-	205	6-ø21	161	SR16	0	2000
BW1747A	5	10	-	205	6-ø21	161	SR16	0	2000
BW1750-DF	5	11	-	222.25	6-ø32	165	SR22	135	2000
BW1750A-DF	5	11	-	222.25	6-ø32	165	SR22	141	2000

17.5 x 6.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1753	6	12	26.4	205	6-ø21.5	161	1x45°	132	2000
BW1756	6	12	-	245	6-ø21.5	202	SR16	139	2000
BW1761	6	12	-	245	6-ø21	202	1x45°	139	2000
BW1776	6	12	-	222.25	6-ø26	161	1x45°	138	2000
BW1777	6	12	-	222.25	6-ø26	164	1x45°	138	2000
BW1781	5	12	-	205	6-ø21	161	1x45°	121	2000
BW1782-DF	5	11	-	222.25	6-ø32	163	SR22	130	2000
BW1784	5	10	22.2	203.2	5-ø32	146	SR22	135	2000
BW1786-ZT	6	12	-	222.25	6-ø24	164	1x45°	135	2000

19.5 x 6.75

STEEL WHEELS

Reccomended tyre size(s): 245/70R19.5 | 265/70R19.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
ABW1903	6	12	30.62	222.25	6-ø32	164	SR22	145	1985
ABW1903A	6	12	30.62	222.25	6-ø32	164	SR22	140	1985
BW1903B	6	12	30.62	222.25	6-ø32	164	SR22	136	1985
BW1903C	6	12	30.62	222.25	6-ø32	164	SR22	152	1985
BW1903D	6	14	33	222.25	6-ø32	164	SR22	136	1985
ABW1904	6	12	30.79	222.25	6-ø24	164	1x45°	145	1985
ABW1905	6	12	29.97	275	8-ø24	221	1x45°	145	1985
BW1905-JL	6	12	29.97	275	8-ø24	221	1x45°	147	1985
ABW1905A	6	12	29.97	275	8-ø24	221	1x45°	140	1985
ABW1913	6	14	35.35	222.25	6-ø32	164	SR22	140	1985
ABW1913A	6	14	35.35	222.25	6-ø32	164	SR22	145	1985
ABW1914	6	14	32.66	285	8-ø32	221	SR22	140	1985
ABW1914A	6	12	30.31	285	8-ø32	221	SR22	145	1985
BW1914B	6	12	30.31	285	8-ø32	221	SR22	140	1985
ABW1916	6	12	30.6	275	8-ø32	214	SR22	140	1985

19.5 x 6.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1916A	6	12	30.6	275	8-ø32	214	SR22	135	1985
ABW1921	6	12	31.35	225	10-ø26	176	1x45°	145	1985
BW1921A	6	14	33.8	225	10-ø26	176	1x45°	140	1985
ABW1923	6	12	29.91	275	8-ø26	221	1x45°	145	1985
BW1923A	6	12	29.91	275	8-ø26	221	SR18	145	1985
BW1923B	6	12	29.91	275	8-ø26	221	1x45°	140	1985
BW1936	6	12	30.9	275	8-ø27	221	SR18	145	1985
BW1939	6	12	31.2	225	10-ø27	176	SR18	145	1985
BW1943	6	12	33.8	205	6-ø21.5	161	SR22	143	1985
BW1964-DF	6	12	30.5	222.25	6-ø26	161	1x45°	130	1985

19.5 x 7.50

STEEL WHEELS

Reccomended tyre size(s): 245/70R19.5 | 255/60R19.5 | 265/70R19.5 | 285/70R19.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
ABW1907	6	12	31.24	275	8-ø24	221	1x45°	152	2500
ABW1907A	6	12	31.17	275	8-ø24	221	SR22	152	2500
ABW1907B	6	12	31.24	275	8-ø24	221	1x45°	146	2500
ABW1907C	6	12	31.17	275	8-ø24	221	SR22	155	2500
BW1907E	6	12	31.24	275	8-ø24	221	1x45°	142	2500
ABW1908	6	12	31.18	275	8-ø26	221	1x45°	152	2500
ABW1908A-DRAGON DREAM	7	12	34	275	8-ø26	221	1x45°	145	3000
BW1908B	6	12	31.18	275	8-ø26	221	SR18	152	2500
ABW1915	6	12	31.89	222.25	6-ø32	164	SR22	152	2500
ABW1917	6	12	33.86	222.25	6-ø32	165	SR22	152	2500
BW1917A	6	12	33.86	222.25	6-ø32	165	SR22	142	2500
ABW1924	6	12	32.62	225	10-ø26	176	1x45°	152	2500
ABW1924A	6	12	32.62	225	10-ø26	176	1x45°	155	2500
BW1924B	6	14	35	225	10-ø26	176	1x45°	156	2500
BW1924D	6	14	35	225	10-ø26	176	1x45°	152	2500

19.5 x 6.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1924E	6	14	35	225	10-ø26	176	1x45°	142	2500
ABW1925	6	12	32.47	225	10-ø27	176	SR18	146	2500
ABW1925A	6	12	32.47	225	10-ø27	176	SR18	151	2500
ABW1927	6	12	31	275	8-ø27	221	SR18	150	2500
BW1938	6	12	31.9	275	8-ø32	214	SR22	145	2500
BW1941	6	12	32.2	275	8-ø26	221	SR22	152	2500
BW1968-DF	6	12	31.9	222.25	6-ø24	164	1x45°	142	2500
BW1968-ZQ3	6	12	31.9	222.25	6-ø24	164	1x45°	142	2500

19.5 x 8.25

STEEL WHEELS

Reccomended tyre size(s): 245/70R19.5 | 255/60R19.5 | 265/70R19.5 | 285/70R19.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
ABW1909	7	14	39.13	225	10-ø26	176	1x45°	165	3000
ABW1909A	8	14	42.6	225	10-ø26	176	1x45°	160	3000
ABW1909B	7	14	39.13	225	10-ø26	176	1x45°	146.5	3000
ABW1909C	7	14	39.13	225	10-ø26	176	1x45°	160	3000
ABW1909D	7	12	36.5	225	10-ø26	176	1x45°	165	3000
BW1909E	7	12	36.5	225	10-ø26	176	1x45°	160	3000
BW1909F	6	14	35.9	225	10-ø26	176	1x45°	146.5	3000
ABW1910	7	14	39.13	225	10-ø26	176	SR16	146.5	3000
ABW1911	7	14	38.28	275	8-ø24	221	1x45°	165	3000
BW1911A	7	12	35.8	275	8-ø24	221	1x45°	165	3000
ABW1912	7	14	38.09	275	8-ø26	221	SR16	165	3000
BW1912B	7	14	38.09	275	8-ø26	221	1x45°	160	3000
BW1912C	7	12	35.7	275	8-ø26	221	SR16	164	3000
BW1912D	7	12	35.7	275	8-ø26	221	1x45°	160	3000
ABW1918	7	14	39.13	225	10-ø26	176	SR18	160	3000

19.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1919	7	12	35.3	208	5-ø32	151	SR22	100	3000
BW1920	7	12	34.8	222.25	6-ø32	164	SR22	100	3000
BW1920A	7	12	34.8	222.25	6-ø32	164	SR22	74	3000
BW1920B	7	12	34.8	222.25	6-ø32	164	SR22	90	3000
BW1926	7	12	30.5	275	8-ø21.5	221	one side SR16	10	-
BW1929	7	12	32.2	205	6-ø21.5	161	one side SR16	10	-
BW1944	7	14	40.6	222.25	6-ø32	164	SR22	160	3000
BW1944A	7	14	40.6	222.25	6-ø32	164	SR22	145	3000
BW1952	7	14	37.3	275	8-ø27	221	SR18	165	3000
BW1953	7	12	30.4	275	8-ø24	221	1x45°	10	3000

19.5 x 14.0

STEEL WHEELS

Reccomended tyre size(s): 425/55R19.5 | 435/50R19.5 | 445/45R19.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1933	7	14	48.8	275	8-ø26	221	1x45°	0	5000
BW1933A	7	14	48.8	275	8-ø26	221	1x45°	5	5000
BW1933B	7	13	48	275	8-ø26	221	SR18	0	5000
BW1933B-01	7	13	48	275	8-ø26	221	1x45°/SR18	0	5000
BW1933C	7	13	48	275	8-ø26	221	SR18	0	5000
BW1933D	7	14	48.8	275	8-ø26	221	1x45°	0	5000
BW1934	7	14	45.7	335	10-ø26	281	1x45°	0	5000
BW1934A	7	14	45.7	335	10-ø26	281	1x45°	120	5000
BW1934B	7	14	45.7	335	10-ø26	281	1x45°	0	5000
BW1935	7	14	45.7	335	10-ø27	281	SR18	0	5000
BW1935A	7	13	44.9	335	10-ø27	281	SR18	120	5000
BW1935B	7	14	46.8	335	10-ø27	281	SR18	0	5000
BW1935-01	7	14	45.7	335	10-ø27	281	1x45°/SR18	0	5000
BW1935D	7	13	44.9	335	10-ø27	281	SR18	0	5000
BW1937-01	7	14	48.8	275	8-ø21.5	221	1x45°/SR16	0	5000

19.5 x 14.0

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW1937A-01	7	13	48.8	275	8-ø21.5	221	1x45°/SR16	0	5000
BW1945	7	14	48.8	275	8-ø21.5	221	1x45°/SR18	0	5000
BW1945A	7	13	47.8	275	8-ø21.5	221	1x45°/SR18	0	5000
BW1948	6	12	44.5	225	10-ø27	176	SR18	0	5000
BW1956	7	14	52	225	10-ø26	176	1x45°	0	5000
BW1956B	7	16	54.4	225	10-ø26	176	1x45°	0	5000
BW1961	7	14	45.7	335	10-ø26	281	SR16	0	5000

22.5 x 6.75

STEEL WHEELS

Reccomended tyre size(s): 9.5R22.5 | 10R22.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2201	6	14	39.01	275	8-ø24	221	1x45°	145	2240
BW2201A	6	12	36.2	275	8-ø24	221	1x45°	145	2240
BW2201B	6	14	39.01	275	8-ø24	221	1x45°	153	2240
BW2201C	6	12	36.2	275	8-ø24	221	1x45°	152	2240
BW2202	6	14	38.94	275	8-ø26	221	1x45°	145	2240
BW2202A	6	12	36.15	275	8-ø26	221	1x45°	145	2240
BW2203	6	14	38.91	275	8-ø27	221	SR18	145	2240
BW2203A	6	14	-	275	8-ø27	221	SR18	145	2240
BW2204	6	14	38.96	275	8-ø32	214	SR22	145	2240
BW2204A	6	14	38.96	275	8-ø32	214	SR22	147	2240
BW2204B	6	12	36.16	275	8-ø32	214	SR22	145	2240
BW2204C	6	14	38.93	275	8-ø32	214	SR22	152	2240
BW2204D	7	14	-	275	8-ø32	214	SR22	147	2240
BW2204E-DF	6	12	-	275	8-ø32	214	SR22	152	2240
BW2204F-DF	6	12	-	275	8-ø32	214	SR22	157	2240

22.5 x 6.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2204G-DF	6	12	-	275	8-ø32	214	SR22	147	2240
BW2205	6	14	38.71	285	8-ø32	221	SR22	145	2240
BW2205A	6	14	38.71	285	8-ø32	221	SR22	142	2240
BW2205B	6	14	37.83	285	8-ø32	221	SR22	150	2240
BW2205C	6	14	38.71	285	8-ø32	221	SR22	152	2240
BW2206	6	14	38.49	285.75	10-ø26	220	1x45°	145	2240
BW2207	6	14	38.04	285.75	10-ø32	222	SR22	145	2240
BW2208	6	14	36.94	335	10-ø26	281	1x45°	145	2240
BW2208A	6	14	36.94	335	10-ø26	281	1x45°	153	2240
BW2208B	6	14	36.94	335	10-ø26	281	1x45°	141	2240
BW2208C	6	12	34.4	335	10-ø26	281	1x45°	145	2240
BW2209	6	14	36.73	335	10-ø27	281	SR18	145	2240

22.5 x 7.50

STEEL WHEELS

Reccomended tyre size(s): 10R22.5 | 11R22.5 | 255/70R22.5 | 275/70R22.5 | 275/80R22.5 | 275/90R22.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2210	7	14	42.61	275	8-ø24	221	1x45°	153	2575
BW2210A	7	16	45.41	275	8-ø24	221	1x45°	153	2575
BW2210B	7	14	42.2	275	8-ø24	221	1x45°	153	2575
BW2210C	7	14	42.61	275	8-ø24	221	1x45°	165	2575
BTW2210C	6	14	39.3	275	8-ø24	221	1x45°	165	2575
BW2210D	7	14	42.2	275	8-ø24	221	1x45°	165	2575
BTW2210D	6	14	38.9	275	8-ø24	221	1x45°	165	2575
BW2210E	7	16	45.41	275	8-ø24	221	1x45°	160	2575
BW2210F	7	14	42.61	275	8-ø24	221	1x45°	160	2575
BW2211	7	14	42.53	275	8-ø32	214	SR22	153	2575
BW2211A	7	16	45.04	275	8-ø32	214	SR22	153	2575
BW2211B	7	14	42.56	275	8-ø32	214	SR22	140	2575
BW2211C	7	14	42.56	275	8-ø32	214	SR22	145	2575
BW2211D	7	14	42.53	275	8-ø32	214	SR22	165	2575
BTW2211D	6	14	39.2	275	8-ø32	214	SR22	165	2575

22.5 x 7.50

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2214	7	14	42.33	285	8-ø32	221	SR22	153	2575
BTW2214	6	14	40	285	8-ø32	221	SR22	153	2575
BW2214A	7	16	44.75	285	8-ø32	221	SR22	153	2575
BW2214B	7	14	42.33	285	8-ø32	221	SR22	165	2575
BW2214B-Q	7	13	-	285	8-ø32	221	SR22	165	2575
BTW2214B	6	14	39	285	8-ø32	221	SR22	165	2575
BW2214C	7	14	42.07	285	8-ø32	221	SR22	162	2575
BTW2214C	6	14	38.8	285	8-ø32	221	SR22	165	2575
BW2214C-KOBA	7	14	42.07	285	8-ø32	221	SR22	162	2575
BW2214D	7	14	42.53	285	8-ø32	221	SR22	162	2575
BW2214D-KOBA	7	14	42.53	285	8-ø32	221	SR22	162	2575
BW2214E	6	14	38.6	285	8-ø32	221	SR22	165	2575
BW2214F	7	16	44.75	285	8-ø32	221	SR22	165	2575
BW2214G	7	14	41.4	285	8-ø32	221	SR22	153	2575
BW2214H	7	16	44.3	285	8-ø32	221	SR22	153	2575
BW2215	7	14	42	285.75	10-ø26	220	1x45°	153	2575

22.5 x 7.50

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2215A	7	14	41.96	285.75	10-ø26	221	1x45°	152	2575
BW2215B	7	14	42	285.75	10-ø26	220	1x45°	165	2575
BTW2215B	6	14	38.7	285.75	10-ø26	220	1x45°	165	2575
BW2215C	7	16	44.2	285.75	10-ø26	220	1x45°	153	2575
BW2216	7	14	41.72	285.75	10-ø32	222	SR22	153	2575
BW2216A	7	14	41.72	285.75	10-ø32	222	SR22	165	2575
BW2216B	7	16	43.9	285.75	10-ø32	222	SR22	153	2575
BW2217	7	14	40.54	335	10-ø26	281	1x45°	153	2575
BTW2217	6	14	37.2	335	10-ø26	281	1x45°	155	2575
BW2217A	7	14	40.54	335	10-ø26	281	1x45°	165	2575
BTW2217A	6	14	37.2	335	10-ø26	281	1x45°	165	2575
BW2217A-Q	6	13	35.9	335	10-ø26	281	1x45°	165	2575
BTW2217A-01	6	14	37.2	335	10-ø26	281	SR18	165	2575
BW2217B	7	14	39.91	335	10-ø26	281	1x45°	165	2575
BW2217C	7	14	40.54	335	10-ø26	281	1x45°	162	2575
BTW2217C	6	14	37.24	335	10-ø26	281	1x45°	162	2575

22.5 x 7.50

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2217D	7	14	40.54	335	10-ø26	281	1x45°	160	2575
BTW2217D	6	14	37.24	335	10-ø26	281	1x45°	160	2575
BW2217E	7	16	42.93	335	10-ø26	281	1x45°	165	2575
BW2217F	7	14	40.66	335	10-ø26	281	1x45°	153	2575
BW2218	7	14	40.33	335	10-ø27	281	SR18	153	2575
BTW2218	6	14	37	335	10-ø27	281	SR18	153	2575
BW2218A	7	14	40.33	335	10-ø27	281	SR18	165	2575
BW2218B	7	14	40.33	335	10-ø27	281	SR18	159	2575
BW2254	7	14	42.54	275	8-ø26	221	1x45°	153	2575
BTW2254	6	14	39.2	275	8-ø26	221	1x45°	153	2575
BW2254A	7	14	42.54	275	8-ø26	221	1x45°	165	2575
BTW2254A	6	14	39.2	275	8-ø26	221	1x45°	165	2575
BW2254B	7	16	45.3	275	8-ø26	221	1x45°	153	2575
BTW2254D	6	14	39.2	275	8-ø26	221	1x45°	162	2575
BW2268	7	14	42.5	275	8-ø27	221	SR18	153	2575
BW2268A	7	14	42.5	275	8-ø27	221	SR18	158	2575

22.5 x 7.50

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2268B	7	14	-	275	8-ø27	221	SR18	153	2575
BW2283	7	14	-	335	10-ø26	281	1x45°	165	2575
BW2283A	7	14	-	335	10-ø26	281	1x45°	162	2575
BTW2283A	6	14	-	335	10-ø26	281	1x45°	162	2575
BW2283B	7	12	-	335	10-ø26	281	1x45°	160	2575
BW2297	6	14	-	225	10-ø26	176	1x45°	145	2240
BW2298	7	14	-	335	10-ø27	281	SR18	165	2575
BW22145	7	14	-	275	8-ø24	221	1x45°	165	2575

22.5 x 8.25

STEEL WHEELS

Reccomended tyre size(s): 11R22.5 | 12R22.5 | 255/70R22.5 | 275/70R22.5 | 275/80R22.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2219	7	14	44.83	275	8-ø24	221	1x45°	169	3000
BW2219A	7	14	44.83	275	8-ø24	221	1x45°	165	3000
BW2219B	7	16	47.6	275	8-ø24	221	1x45°	160	3000
BW2219C	8	16	50.7	275	8-ø24	221	1x45°	160	3000
BW2219E	7	14	44.83	275	8-ø24	221	1x45°	160	3000
BW2219F-ZT	7	14	44.83	275	8-ø24	221	1x45°	163	3000
BW2219Q	6	14	42.15	275	8-ø24	221	1x45°	169	3000
BW2220	7	14	44.72	275	8-ø27	221	SR18	169	3000
BW2220A	7	14	-	275	8-ø27	221	SR18	169	3000
BW2220Q	6	14	42.04	275	8-ø27	221	SR18	169	3000
BW2221	7	14	44.75	275	8-ø32	214	SR22	169	3000
BW2221A	7	16	47.26	275	8-ø32	214	SR22	169	3000
BW2221B	7	14	44.75	275	8-ø32	214	SR22	160	3000
BW2221Q	6	14	42.07	275	8-ø32	214	SR22	169	3000
BW2222	7	14	44.55	285	8-ø32	221	SR22	169	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2222-Q	7	13	-	285	8-ø32	221	SR22	169	3000
BW2222A	7	16	46.97	285	8-ø32	221	SR22	169	3000
BW2222B	7	14	44.29	285	8-ø32	221	SR22	165	3000
BW2222B-KOBA	7	14	44.29	285	8-ø32	221	SR22	165	3000
BTW2222B	6	13	40.2	285	8-ø32	221	SR22	169	3000
BTW2222B-01	6	14	-	285	8-ø32	221	SR22	165	3000
BW2222C	8	16	50.08	285	8-ø32	221	SR22	169	3000
BW2222D	7	14	43.65	285	8-ø32	221	SR22	169	3000
BW2222E	7	16	46.56	285	8-ø32	221	SR22	169	3000
BW2222F	7	14	44.55	285	8-ø32	221	SR22	165	3000
BTW2222F-DRAGON DREAM	6	14	41.8	285	8-ø32	221	SR22	165	3650
BW2222F-KOBA	7	14	44.55	285	8-ø32	221	SR22	165	3000
BW2222G	7	14	44.19	285	8-ø32	221	SR22	169	3000
BTW2222G	6	14	41.5	285	8-ø32	221	SR22	169	3000
BW2222H	7	16	46.9	285	8-ø32	221	SR22	169	3000
BW2222I	8	16	50.08	285	8-ø32	221	SR22	165	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2222J	7	16	46.97	285	8-ø32	221	SR22	165	3000
BW2222K	8	16	50.12	285	8-ø32	221	SR22	165	3000
BW2222L	7	16	46.97	285	8-ø32	221	SR22	150	3000
BW2222M	7	14	-	285	8-ø32	221	SR22	169	3000
BTW2222M	6	14	-	285	8-ø32	221	SR22	169	3000
BW2222N	7	14	44.29	285	8-ø32	221	SR22	169	3000
BW2222Q	6	14	41.87	285	8-ø32	221	SR22	169	3000
BW2222S	6	14	40.9	285	8-ø32	221	SR22	169	3000
BW2222T	7	16	47	285	8-ø32	221	SR22	169	3000
BW2222V	6	12	39.11	285	8-ø32	221	SR22	169	3000
BW2222W	6	14	41.87	285	8-ø32	222	SR22	169	3000
BW2222X	7	16	46.97	285	8-ø32	222	SR22	169	3000
BW2223	7	14	44.22	285.75	10-ø26	220	1x45°	169	3000
BW2223A	7	16	46.42	285.75	10-ø26	220	1x45°	169	3000
BW2223B	8	16	49.53	285.75	10-ø26	220	1x45°	169	3000
BW2223C	6	11	37.64	285.75	10-ø26	220	1x45°	168	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2223D	7	14	44.21	285.75	10-ø26	220	1x45°	168	3000
BW2223D-Q	6	13	39.8	285.75	10-ø26	220	1x45°	168	3000
BW2223E	7	14	44.22	285.75	10-ø26	220	1x45°	165	3000
BTW2223E	6	14	41.5	285.75	10-ø26	220	1x45°	165	3000
BW2223F	7	14	44.18	285.75	10-ø26	221	1x45°	168	3000
BTW2223F	6	14	41.5	285.75	10-ø26	221	1x45°	168	3000
BTW2223F-Q	6	13	40.1	285.75	10-ø26	221	1x45°	168	3000
BW2223G	6	11	37.64	285.75	10-ø26	220	1x45°	168	3000
BW2223H	5.5	11	35.5	285.75	10-ø26	220	1x45°	168	3000
BW2223I	7	14	44.7	285.75	10-ø26	220	1x45°	168	3000
BW2223J	7	14	44.02	285.75	10-ø26	220	1x45°	169	3000
BW2223K	7	16	47.3	285.75	10-ø26	220	1x45°	169	3000
BW2223L	5.5	11	33.9	285.75	10-ø26	220	1x45°	168	3000
BW2223M	7	14	-	285.75	10-ø26	220	1x45°	169	3000
BW2223P	5.5	11	35	285.75	10-ø26	220	1x45°	168	3000
BW2223Q	6	14	41.54	285.75	10-ø26	220	1x45°	169	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2223Q-Q	6	13	40.1	285.75	10-ø26	220	1x45°	169	3000
BW2223R	7	14	44.21	285.75	10-ø26	220	1x45°	168	3000
BW2223S	8	16	-	285.75	10-ø26	220	1x45°	168	3000
BW2223T	6	12	39.2	285.75	10-ø26	220	1x45°	168	3000
BW2223U	6	12	38.7	285.75	10-ø26	220	1x45°	168	3000
BW2223V	6	11	36.64	285.75	10-ø26	220	1x45°	168	3000
BW2223W	5.5	11	33.9	285.75	10-ø26	220	1x45°	168	3000
BW2223Y	6	12	38.8	285.75	10-ø26	220	1x45°	168	3000
BW2224	7	14	43.94	285.75	10-ø32	222	SR22	169	3000
BW2224A	7	16	46.2	285.75	10-ø32	222	SR22	169	3000
BW2224B	7	14	44.08	285.75	10-ø32	222	SR22	169	3000
BW2224C	8	16	49.31	285.75	10-ø32	222	SR22	169	3000
BW2224D	7	14	43.64	285.75	10-ø32	222	SR22	169	3000
BTW2224D	6	14	40.9	285.75	10-ø32	222	SR22	169	3000
BW2224E	7	16	46.33	285.75	10-ø32	222	SR22	169	3000
BW2224F	7	14	43.94	285.75	10-ø32	222	SR22	165	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BTW2224F	6	14	41.2	285.75	10-ø32	222	SR22	165	3000
BW2224G	7	14	43.94	285.75	10-ø32	222	SR22	160	3000
BW2224H	6	11	37.74	285.75	10-ø32	222	SR22	169	3000
BW2224I	7	16	46.2	285.75	10-ø32	222	SR22	165	3000
BW2224J	7	14	44.55	285.75	10-ø32	222	SR22	168	3000
BW2224K	6	11	37.84	285.75	10-ø32	221	SR22	168	3000
BW2224L	7	14	-	285.75	10-ø32	222	SR22	169	3000
BTW2224L	6	14	-	285.75	10-ø32	222	SR22	169	3000
BW2224M	6	11	37.74	285.75	10-ø32	222	SR22	169	3000
BW2224N	6	11	37.74	285.75	10-ø32	221	SR22	168	3000
BW2224P	7	14	43.94	285.75	10-ø32	222	SR22	158	3000
BW2224Q	6	14	41.26	285.75	10-ø32	222	SR22	169	3000
BW2224Q-Q	6	13	39.9	285.75	10-ø32	222	SR22	169	3000
BW2224R	5.5	11	35.5	285.75	10-ø32	222	SR22	168	3000
BW2224S	5.5	11	34.5	285.75	10-ø32	222	SR22	168	3000
BW2224T	7	16	46.2	285.75	10-ø32	221	SR22	169	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2224U	6	14	41.2	285.75	10-ø32	221	SR22	169	3000
BW2225	7	14	42.76	335	10-ø26	281	1x45°	169	3000
BW2225-Q	7	13	-	335	10-ø26	281	1x45°	169	3000
BW2225Q-Q	6	13	38.8	335	10-ø26	281	1x45°	169	3000
BW2225A	7	16	45.15	335	10-ø26	281	1x45°	169	3000
BW2225B	8	16	48.26	335	10-ø26	281	1x45°	169	3000
BW2225C	7	14	43.67	335	10-ø26	281	1x45°	168	3000
BW2225D	7	14	42.88	335	10-ø26	281	1x45°	169	3000
BTW2225D	6	14	40.2	335	10-ø26	281	1x45°	169	3000
BW2225E	7	16	44.65	335	10-ø26	281	1x45°	169	3000
BW2225F	6	11	38.44	335	10-ø26	281	1x45°	169	3000
BW2225G	6	14	39.45	335	10-ø26	281	1x45°	170	3000
BW2225H	7	16	45.15	335	10-ø26	281	1x45°	165	3000
BW2225I	7	14	42.76	335	10-ø26	281	1x45°	165	3000
BTW2225I	6	14	40	335	10-ø26	281	1x45°	165	3000
BW2225J	7	14	42.76	335	10-ø26	281	1x45°	171	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2225J-1	7	14	42.76	335	10-ø26	281	1x45°	172.5	3000
BW2225K	7	14	42.13	335	10-ø26	281	1x45°	169	3000
BW2225L	7	16	44.55	335	10-ø26	281	1x45°	169	3000
BW2225P	8	16	48.26	335	10-ø26	281	1x45°	165	3000
BW2225Q	6	14	40.08	335	10-ø26	281	1x45°	169	3000
BW2225S	7	14	42.76	335	10-ø26	281	SR18	165	3000
BW2225T	8	14	45.8	335	10-ø26	281	1x45°	169	3000
BW2225U	7	14	42.76	335	10-ø26	281	1x45°	152	3000
BW2225V	6	12	39	335	10-ø26	281	1x45°	172.5	3000
BW2225W	6	12	39	335	10-ø26	281	1x45°	168	3000
BW2226	7	14	42.55	335	10-ø27	281	SR18	169	3000
BW2226A	7	16	44.37	335	10-ø27	281	SR18	169	3000
BW2226B	8	16	47.484	335	10-ø27	281	SR18	169	3000
BW2226C	7	14	42.27	335	10-ø27	281	SR18	169	3000
BTW2226C	6	14	39.5	335	10-ø27	281	SR18	169	3000
BW2226D	7	16	44.56	335	10-ø27	281	SR18	169	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2226E	7	14	42.55	335	10-ø27	281	SR18	165	3000
BW2226F	7	14	42.09	335	10-ø27	281	SR18	165	3000
BW2226G	6	14	39.4	335	10-ø27	281	SR18	169	3000
BW2226H	7	14	42	335	10-ø27	281	SR18	169	3000
BW2226Q	6	14	39.87	335	10-ø27	281	SR18	169	3000
BW2227	7	14	46.59	285.75	10-ø26	220	1x45°	171	3000
BTW2227	6	14	43.21	285.75	10-ø26	220	1x45°	171	3000
BW2228	7	14	46.23	285.75	10-ø32	222	SR22	171	3000
BTW2228	6	14	42.85	285.75	10-ø32	222	SR22	171	3000
BW2228 ERAV	7	14	46.28	285.75	10-ø32	220	SR22	171	3000
BW2229	7	14	43.31	335	10-ø26	281	1x45°	168	3000
BTW2229	6	14	39.8	335	10-ø26	281	1x45°	168	3550
BW2229A	7	16	44.94	335	10-ø26	281	1x45°	168	3000
BW2229A-SL	7	16	44.94	335	10-ø26	281	1x45°	168	3000
BW2229C	7	14	43.31	335	10-ø26	281	1x45°	165	3000
BW2229D-ZT	8	16	48.2	335	10-ø26	281	1x45°	168	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2253	7	14	-	335	10-ø27	281	SR18	168	3000
BW2261	7	14	44.68	275	8-ø26	221	1x45°	169	3000
BTW2261	6	14	42	275	8-ø26	221	1x45°	169	3000
BW2261A	7	14	44.68	275	8-ø26	221	1x45°	165	3000
BW2261B	6	11	-	275	8-ø26	221	1x45°	168	3000
BW2267	7	13.5	-	335	10-ø26	281	1x45°	165	3000
BW2272	7	14	44.32	275	8-ø26.5	221	1x45°	160	3000
BW2272A	7	16	47	275	8-ø26.5	221	1x45°	160	3000
BW2272B	8	16	50.13	275	8-ø26.5	221	1x45°	160	3000
BW2277	7	14	-	335	10-ø26	281	1x45°	170	3000
BTW2277	6	14	-	335	10-ø26	281	1x45°	170	3000
BW2277D-WL	7	16	-	335	10-ø26	281	1x45°	162	3000
BW22100	6	12	41.02	203.2	8-ø16.5	152.4	90°	38	3000
BW22101	6	12	41.2	152.4	6-ø14.7	117.7	90°	28.5	3000
BW22112	5	11	33	285.75	10-ø26	220	1x45°	169	3000
BW22112A	4.3	11	32	285.75	10-ø26	220	1x45°	169	3000

22.5 x 8.25

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW22112B	4.3	11	31	285.75	10-ø26	220	1x45°	169	3000
BW22112C	5	11	32	285.75	10-ø26	220	1x45°	169	3000
BW22119	5	11	33.5	335	10-ø26	281	1x45°	165	3000
BW22120	5	11	33	285.75	10-ø32	222	SR22	169	3000
BW22120A	4.3	11	32	285.75	10-ø32	222	SR22	168	3000
BW22143	7	16	-	285	8-ø32	221	SR22	117	3000
BW22148B	7	16	-	335	10-ø26	281	1x45°	115	3000
BW22212	4.5	11	32	285.75	10-ø26	220	1x45°	169	3000
BW22212A	4.5	11	31	285.75	10-ø26	220	1x45°	169	3000
BW22212B	5	11	33	285.75	10-ø26	220	1x45°	169	3000
BW22212C	5	11	32	285.75	10-ø26	220	1x45°	169	3000
BW22212E	4.5	11	31.5	285.75	10-ø26	220	1x45°	169	3000
BW22212G	5	11	32	285.75	10-ø26	220	1x45°	169	3000
BW22213-RIMCO	4.5	11	32	285.75	10-ø32	222	SR22	169	3000

22.5 x 9.00

STEEL WHEELS

Reccomdended tyre size(s): 12R22.5 | 13R22.5 | 295/55R22.5 | 295/60R22.5 | 295/80R22.5 | 305/70R22.5 |

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2230	7	14	46.51	275	8-ø24	221	1x45°	175	3750
BW2230Q	6	14	42.81	275	8-ø24	221	1x45°	175	3750
BW2231	7	14	46.43	275	8-ø32	214	SR22	175	3750
BW2231Q	6	14	42.73	275	8-ø32	214	SR22	175	3750
BW2232	7	14	46.23	285	8-ø32	221	SR22	175	3750
BW2232A	7	16	48.65	285	8-ø32	221	SR22	175	3750
BW2232B	7	14	45.97	285	8-ø32	221	SR22	175	3750
BTW2232B	6	14	42.2	285	8-ø32	221	SR22	175	3750
BW2232C	8	16	52.19	285	8-ø32	221	SR22	175	3750
BW2232D	7	14	45.33	285	8-ø32	221	SR22	175	3750
BTW2232D	6	14	41.6	285	8-ø32	221	SR22	175	3750
BW2232E	7	16	48.24	285	8-ø32	221	SR22	175	3750
BW2232G	7	16	48.65	285	8-ø32	221	SR22	150	3750
BW2232H	7	16	48.58	285	8-ø32	221	SR22	175	3750
BW2232I	8	16	52.19	285	8-ø32	221	SR22	160	3750

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2232J	7	14	46.23	285	8-ø32	221	SR22	150	3750
BW2232L	8	16	52.2	285	8-ø32	221	SR22	175	3750
BW2232M	7	16	48.65	285	8-ø32	221	SR22	180	3750
BW2232N	7	14	46.23	285	8-ø32	221	SR22	180	3750
BW2232P	7	16	48.65	285	8-ø32	221	SR22	160	3750
BW2232Q	6	14	42.53	285	8-ø32	221	SR22	175	3750
BW2232Q-Q	6	13	41.2	285	8-ø32	221	SR22	175	3750
BW2232R	7	16	48.6	285	8-ø32	221	SR22	175	3750
BW2233	7	14	45.9	285.75	10-ø26	220	1x45°	175	3750
BW2233A	7	16	48.1	285.75	10-ø26	220	1x45°	175	3750
BW2233B	8	16	51.64	285.75	10-ø26	220	1x45°	175	3750
BW2233C	7	14	45.86	285.75	10-ø26	221	1x45°	175	3750
BW2233E	7	16	48.4	285.75	10-ø26	220	1x45°	175	3750
BW2233F	7	14	45.9	285.75	10-ø26	220	1x45°	175	3750
BW2233G	7	14	46.4	285.75	10-ø26	220	1x45°	175	3750
BTW2233G	6	14	42.7	285.75	10-ø26	220	1x45°	175	3750

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2233H	7	14	45.3	285.75	10-ø26	220	1x45°	175	3750
BTW2233H	6	14	41.6	285.75	10-ø26	220	1x45°	175	3750
BW2233I	7	16	-	285.75	10-ø26	220	1x45°	175	3750
BW2233Q	6	14	42.2	285.75	10-ø26	220	1x45°	175	3750
BW2233Q-Q	6	13	40.84	285.75	10-ø26	220	1x45°	175	3750
BW2233R	8	16	-	285.75	10-ø26	220	1x45°	175	3750
BW2233S	7	16	-	285.75	10-ø26	220	1x45°	175	3750
BW2233T	7	16	48.1	285.75	10-ø26	221	1x45°	175	3750
BW2234	7	14	45.62	285.75	10-ø32	222	SR22	175	3750
BW2234A	7	16	47.88	285.75	10-ø32	222	SR22	175	3750
BW2234B	8	16	51.42	285.75	10-ø32	222	SR22	175	3750
BW2234C	7	14	45.32	285.75	10-ø32	222	SR22	175	3750
BW2234D	7	16	48.01	285.75	10-ø32	222	SR22	175	3750
BW2234F	7	16	-	285.75	10-ø32	222	SR22	177	3750
BW2234G	7	14	45.62	285.75	10-ø32	222	SR22	175	3750
BW2234H	7	14	46.2	285.75	10-ø32	222	SR22	175	3750

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2234I	7	14	46.2	285.75	10-ø32	222	SR22	175	3750
BTW2234I	6	14	42.5	285.75	10-ø32	222	SR22	175	3750
BW2234K	7	14	45.62	285.75	10-ø32	222	SR22	158	3750
BW2234M	7	16	49	285.75	10-ø32	222	SR22	175	3750
BW2234N	7	16	47.88	285.75	10-ø32	221	SR22	175	3750
BTW2234P	6	14	44.3	285.75	10-ø32	222	SR22	175	3750
BW2234Q	6	14	41.92	285.75	10-ø32	222	SR22	175	3750
BW2235	7	14	44.44	335	10-ø26	281	1x45°	175	3750
BW2235A	7	16	46.83	335	10-ø26	281	1x45°	175	3750
BW2235B	8	16	50.37	335	10-ø26	281	1x45°	175	3750
BW2235C	8	14	47.98	335	10-ø26	281	1x45°	175	3750
BW2235D	7	14	44.56	335	10-ø26	281	1x45°	175	3750
BTW2235D	6	14	40.8	335	10-ø26	281	1x45°	175	3750
BW2235DF	7	14	44.44	335	10-ø26	281.1	1x45°	175	3750
BW2235E	7	16	46.33	335	10-ø26	281	1x45°	175	3750
BW2235F	6	12	42.2	335	10-ø26	281	1x45°	175	3750

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2235G	5.5	11	37.2	335	10-ø26	281	1x45°	175	3750
BW2235H	7	14	44.44	335	10-ø26	281	1x45°	172	3750
BW2235I	7	14	43.81	335	10-ø26	281	1x45°	175	3750
BW2235I-SFC	7	14	43.81	335	10-ø26	281	1x45°	175	3750
BW2235J	7	16	46.83	335	10-ø26	281	1x45°	170	3750
BW2235K	7	16	46.23	335	10-ø26	281	1x45°	175	3750
BW2235L-Q	6	13	-	335	10-ø26	281	1x45°	175	3750
BW2235M	7	14	44.44	335	10-ø26	281	1x45°	168	3750
BW2235N	7	15	-	335	10-ø26	281	1x45°	175	3750
BW2235Q	6	14	40.74	335	10-ø26	281	1x45°	175	3750
BW2235Q-Q	6	13	-	335	10-ø26	281	1x45°	175	3750
BW2235R	7	14	44.44	335	10-ø26	281	1x45°	180	3750
BW2235S	8	16	50.37	335	10-ø26	281	1x45°	169	3750
BW2235T	8	16	49.8	335	10-ø26	281	1x45°	175	3750
BW2235U	7	16	46.83	335	10-ø26	281	1x45°	180	3750
BW2236	7	14	44.23	335	10-ø27	281	SR18	175	3750

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2236A	7	16	46.05	335	10-ø27	281	SR18	175	3750
BW2236B	8	16	49.59	335	10-ø27	281	SR18	175	3750
BW2236C	7	14	43.95	335	10-ø27	281	SR18	175	3750
BW2236D	7	16	46.28	335	10-ø27	281	SR18	175	3750
BW2236E	7	16	46.05	335	10-ø27	281	SR18	150	3750
BW2236F	7	14	44.23	335	10-ø27	281	SR18	180	3750
BW2236Q	6	14	40.53	335	10-ø27	281	SR18	175	3750
BW2236Q-Q	6	13	-	335	10-ø27	281	SR18	175	3750
BW2237	7	14	45.3	335	10-ø26	281	1x45°	175	3750
BW2237Q-Q	6	13	40.2	335	10-ø26	281	1x45°	175	3750
BTW2237	6	14	41.5	335	10-ø26	281	1x45°	175	3750
BTW2237-01	6	14	41.5	335	10-ø26	281	1x45°	177.5	3750
BW2237A	7	16	46.93	335	10-ø26	281	1x45°	175	3750
BW2238	7	14	46.89	335	10-ø26	281	1x45°	180	4000
BW2238A	7	16	49.28	335	10-ø26	281	1x45°	180	4000
BW2238B	8	16	52.39	335	10-ø26	281	1x45°	180	4000

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2238D	8	18	56.86	335	10-ø26	281	1x45°	180	4000
BW2238E	7	14	46.89	335	10-ø26	281	1x45°	185	4000
BW2238F	8	16	52.5	335	10-ø26	281	1x45°	125	4000
BW2238G	9	18	-	335	10-ø26	281	1x45°	175	4000
BW2238H	9	18	-	335	10-ø26	281	1x45°	180	4000
BW2238I	8	18	56.8	335	10-ø26	281	1x45°	175	4000
BW2250	7	14	45.26	335	10-ø27	281	SR18	175	3750
BTW2250	6	14	41.4	335	10-ø27	281	SR18	175	3750
BW2250A	7	14	45.26	335	10-ø27	281	SR18	175	3750
BW2252	7	14	44.07	335	10-ø26	281	1x45°	175	3750
BW2252Q-Q	6	13	-	335	10-ø26	281	1x45°	175	3750
BW2252A	7	16	46.46	335	10-ø26	281	1x45°	175	3750
BW2252B	6	12	-	335	10-ø26	281	1x45°	175	3750
BW2252C	5.5	11	37	335	10-ø26	281	1x45°	175	-
BW2252C-ZQ	5.5	11	37	335	10-ø26	281	1x45°	172	-
BW2256	7	14	49.49	285.75	10-ø26	220	1x45°	180	4000

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2262	7	16	45.96	335	10-ø26	281	1x45°	175	3750
BW2263	7	14	44.4	335	10-ø26	281	1x45°	0	3750
BW2263-01	7	14	44.4	335	10-ø26	281	one side SR18	0	3750
BW2263A	7	14	44.4	335	10-ø26	281	1x45°	125	3750
BW2263B	7	14	-	335	10-ø26	281	1x45°	120	3750
BW2263C	7	16	46.96	335	10-ø26	281	1x45°	125	3750
BW2263D	7	14	-	335	10-ø26	281	1x45°	104	3750
BW2263E	7	14	-	335	10-ø26	281	1x45°	30	3750
BW2263F	8	16	50.5	335	10-ø26	281	1x45°	125	3750
BW2263G	7	16	46.9	335	10-ø26	281	1x45°	0	3750
BW2263H	7	16	45.7	335	10-ø26	281	1x45°	117	3750
BW2266A	9	18	57	335	10-ø26	281	1x45°	175	3750
BW2266B	8	18	54.84	335	10-ø26	281	1x45°	175	3750
BW2266C	9	18	57	335	10-ø26	281	1x45°	180	3750
BW2266E	9	17.5min	57	335	10-ø26	281	1x45°	175	3750
BW2278	7	16	47.83	335	10-ø26	281	1x45°	175	3750

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2278A	7	14	45.4	335	10-ø26	281	1x45°	175	3750
BW2279	7	14	-	335	10-ø26	281	1x45°	175	3750
BTW2279	6	14	-	335	10-ø26	281	1x45°	175	3750
BTW2279C-BC	5.5	12	39	335	10-ø26	281	1x45°	175	3750
BW2279F	5.5	13	38.5	335	10-ø26	281	1x45°	175	4000
BW2280	7	12	-	275	8-ø21.5	222	one side SR16	0	3750
BW2280A	6	14	-	275	8-ø21.5	222	one side SR16	0	3750
BW2288	6	12	40	335	10-ø26	281	1x45°	175	3750
BW2288A	7	16	-	335	10-ø26	281	1x45°	175	3750
BW2290	7	14	-	335	10-ø27	281	SR18	0	3750
BW2290-01	7	14	-	335	10-ø27	281	1x45°/SR18	0	3750
BTW2290-01	6	14	-	335	10-ø27	281	1x45°/SR18	0	3750
BW2275	7	14	-	275	8-ø26	221	1x45°	80	4000
BW2294	7	14	-	275	8-ø26	221	SR18	0	3750
BTW2294	6	14	-	275	8-ø26	221	SR18	0	3750
BW2294A	7	14	-	275	8-ø26	221	1x45°	0	3750

22.5 x 9.00

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BTW2294A	6	14	-	275	8-ø26	221	1x45°	0	3750
BW22103	7	16	-	335	10-ø27	281	SR18	125	3750
BW22103A	7	14	-	335	10-ø27	281	SR18	120	3750
BW22116	6	14	43	335	10-ø26	281	SR18	175	4000
BW22144	7	16	-	285	8-ø32	221	SR22	120	3750
BW22144A	7	14	-	285	8-ø32	221	SR22	120	3750
BW22159-JH	5.5	13	38	335	10-ø26	281	1x45°	175	3550
BW22159-JL	6	13	39.5	335	10-ø26	281	1x45°	175	3750
BW22159-SQ	6	13	39.5	335	10-ø26	281	1x45°	175	4250

22.5 x 11.75

STEEL WHEELS

Reccomended tyre size(s): 355/50R22.5 | 365/70R22.5 | 375/45R22.5 | 375/50R22.5 | 375/90R22.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2239	7	14	50.34	335	10-ø26	281	1x45°	120	4250
BTW2239	6	14	-	335	10-ø26	281	1x45°	120	4250
BW2239A	7	14	50.34	335	10-ø26	281	1x45°	0	4250
BTW2239A	6	12	-	335	10-ø26	281	1x45°	0	4250
BTW2239A-A	6	14	-	335	10-ø26	281	1x45°	0	4250
BW2239B	7	14	50.34	335	10-ø26	281	1x45°	0	4250
BW2239D	7	14	50.34	335	10-ø26	281	1x45°	135	4250
BTW2239D	6	14	-	335	10-ø26	281	1x45°	135	4250
BW2239G	7	14	50.34	335	10-ø26	281	1x45°	0	4250
BTW2239G	6	14	45.68	335	10-ø26	281	1x45°	0	4250
BW2239I	7	16	52.73	335	10-ø26	281	1x45°	135	4250
BW2240	7	14	50.13	335	10-ø27	281	SR18	120	4250
BW2240A	7	14	50.13	335	10-ø27	281	SR18	0	4250
BW2240B	7	14	50.13	335	10-ø27	281	one side SR18	120	4250
BW2240C	7	14	50.13	335	10-ø27	281	one side SR18	0	4250

22.5 x 11.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BTW2240C	6	14	45.4	335	10-ø27	281	one side SR18	0	4250
BW2241	7	14	47.78	335	10-ø26	281	1x45°	120	4250
BTW2241	6	14	43	335	10-ø26	281	1x45°	120	4250
BW2241A	7	14	47.78	335	10-ø26	281	1x45°	0	4250
BTW2241A	6	14	43	335	10-ø26	281	1x45°	0	4250
BW2241B	7	12	45.64	335	10-ø26	281	1x45°	0	4250
BTW2241B	6	12	40.9	335	10-ø26	281	1x45°	0	4250
BW2241C	7	14	47.78	335	10-ø26	281	1x45°	120	4250
BTW2241C	6	14	43	335	10-ø26	281	1x45°	120	4250
BW2241D	7	14	-	335	10-ø26	281	1x45°	0	4250
BTW2241D	6	13	-	335	10-ø26	281	1x45°	0	4250
BW2241E	7	12	46.51	335	10-ø26	281	1x45°	0	4250
BW2241F	7	16	49.92	335	10-ø26	281	1x45°	0	4250
BW2241G	8	16	54.88	335	10-ø26	281	1x45°	0	4250
BW2241H	7	14	47.78	335	10-ø26	281	1x45°	0	4250
BW2241I	7	16	49.92	335	10-ø26	281	1x45°	120	4250

22.5 x 11.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2241J	7	14	47.7	335	10-ø26	281	SR18	0	4250
BTW2241J	6	14	-	335	10-ø26	281	SR18	0	4250
BW2241K	8	16	54.88	335	10-ø26	281	1x45°	120	4250
BW2241L	7	14	-	335	10-ø26	281	SR18	120	4250
BW2241N-01	7	14	48	335	10-ø26	281	1x45°	120	4250
BW2241N-02	7	14	48	335	10-ø26	281	1x45°	130	4250
BTW2241N-02	6	14	43.2	335	10-ø26	281	1x45°	130	4250
BTW2241N-03	6	14	43.2	335	10-ø26	281	1x45°	135	4250
BW2241Q-01	7	14	48	335	10-ø26	281	1x45°	0	4250
BW2241Q-02	7	14	48	335	10-ø26	281	one side SR18	0	4250
BW2241R	7	14	47.78	335	10-ø26	281	1x45°	0	4250
BTW2241R	6	14	43	335	10-ø26	281	1x45°	0	4250
BW2242	7	14	47.73	335	10-ø27	281	SR18	120	4250
BW2242A	7	14	47.73	335	10-ø27	281	SR18	0	4250
BW2242B	7	12	45.6	335	10-ø27	281	SR18	0	4250
BW2242C	7	14	46.73	335	10-ø27	281	SR18	0	4250

22.5 x 11.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BTW2242C	6	14	42	335	10-ø27	281	SR18	0	4250
BW2243D	7	14	-	335	10-ø26	281	1x45°	98	4250
BW2243E	7	16	-	335	10-ø26	281	1x45°	0	4250
BW2244	7	14	46.86	335	10-ø26	281	1x45°	120	4250
BTW2244	6	14	43.6	335	10-ø26	281	1x45°	120	4250
BW2244A	7	14	46.86	335	10-ø26	281	1x45°	0	4250
BTW2244A	6	13	42.6	335	10-ø26	281	1x45°	0	4250
BW2244A-Q	6	13	-	335	10-ø26	281	1x45°	0	4250
BW2244B	7	14	46.86	335	10-ø26	281	1x45°	120	4250
BW2244C	7	12	-	335	10-ø26	281	SR18	0	4250
BW2244D	7	14	46.86	335	10-ø26	281	SR18	120	4250
BW2244E	7	14	46.86	335	10-ø26	281	1x45°	79	4250
BTW2244E	6	14	42.3	335	10-ø26	281	1x45°	79	4250
BW2244F	7	14	-	335	10-ø26	281	1x45°	134	4250
BTW2244F	6	14	-	335	10-ø26	281	1x45°	134	4250
BW2244G	7	14	-	335	10-ø26	281	SR18	134	4250

22.5 x 11.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2244H	7	14	-	335	10-ø26	281	SR18	0	4250
ABW2249	7	14	-	285.75	10-ø26	220	1x45°	120	4250
BW2255A	7	14	52.41	275	8-ø24	221	1x45°	0	4250
BW2255B	6	12	-	275	8-ø24	221	1x45°	0	4250
BW2260	7	14	-	335	10-ø27	281	SR18	0	4250
ABTW2270A	6	14	-	275	8-ø21.5	221	one side SR16	0	4250
BTW2270-HBI	7	14	-	275	8-ø21.5	221	one side SR16	0	4250
BW2281	7	14	-	275	8-ø26.5	221	SR18	0	4250
BTW2281	6	14	-	275	8-ø26.5	221	SR18	0	4250
BW2286	7	14	-	275	8-ø21.5	221	SR16	0	4250
BTW2286	6	14	-	275	8-ø21.5	221	SR16	0	4250
BTW2286-01	6	14	-	275	8-ø21.5	221	one side SR16	0	4250
BW2291	7	14	-	275	8-ø26	221	1x45°	80	4250
BW2291A	7	14	-	275	8-ø26	221	1x45°	80	4250
BW2292	7	14	-	275	8-ø21.5	221	SR16	0	4250
BTW2292	6	14	-	275	8-ø21.5	221	SR16	0	4250

22.5 x 11.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW22102	6	12	45.7	203.2	8-ø16.5	152.4	90°	28.5	4250
BW22102-RIMCO	6	12	45.7	203.2	8-ø16.5	152.4	90°	28.5	4250
BW22115	6	14	44	335	10-ø26	281	1x45°	120	-
BW22115-TUV	6	13	44	335	10-ø26	281	1x45°	120	-
BW22115-OE	6	14	44	335	10-ø26	281	1x45°	120	-
BW22115A	6	14	44	335	10-ø26	281	1x45°	0	-
BW22115A-OE	6	14	44	335	10-ø26	281	1x45°	0	-
BW22115B	6	16	45.5	335	10-ø26	281	1x45°	120	-
BW22117	6	14	44	335	10-ø26	281	SR18	120	-
BW22117A	6	14	44	335	10-ø26	281	SR18	0	-
BW22117B	6	14	44	335	10-ø27	281	SR18	120	-
BW22117C	6	14	44	335	10-ø27	281	SR18	0	-
BW22129	6	12	-	203.2	8-ø20.6	152.4	1x45°	28.5	4250
BW22131	6	12	-	275	8-ø21.5	221	one side SR16	0	4250
BW22132	6	12	-	275	8-ø27	221	SR18	50	4250
BW22132A	6	12	-	275	8-ø27	221	one side SR18	0	4250

22.5 x 11.75

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW22134	6	12	-	335	10-ø27	281	one side SR18	0	4250
BW22141-RIMCO	6	12	-	285.75	10-ø32	222	one side SR22	0	

22.5 x 13.0

STEEL WHEELS

Reccomended tyre size(s): 425/65R22.5 | 445/65R22.5 | 445/75R22.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2245	7	16	56.06	335	10-ø26	281	1x45°	75	5150
BW2245A	7	16	56.06	335	10-ø26	281	1x45°	0	5150
BW2245A-JH	7	16	57.3	335	10-ø26	281	1x45°	0	5150
BW2245B	8	16	61.16	335	10-ø26	281	1x45°	0	5150
BW2245C	7	16		335	10-ø26	281	1x45°	0	5150
BW2245D	7	16		335	10-ø26	281	1x45°	120	5150
BW2245E	7	16	53	335	10-ø26	281	1x45°	120	5150
BW2245G	8	16		335	10-ø26	281	1x45°	120	5150
BW2245H	7	16	56.06	335	10-ø26	281	1x45°	12	5150
BW2245I	7	14	53.5	335	10-ø26	281	1x45°	0	5150
BW2245L	7	16		335	10-ø26	281	1x45°	120	5150
BW2245N	7	14		335	10-ø26	281	1x45°	120	5150
BW2246	7	16	56.02	335	10-ø27	281	SR18	0	5150
BW2296A	7	16	57.2	285.75	10-ø26	220	1x45°	14	5150
BW2296C	7	16		285.75	10-ø26	220	1x45°	25	5150

22.5 x 13.0

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW22107	6.6	14	61.5	203.2	8-ø20.6	152.7	1x45°	8	5150
BW22108	6.6	14	60.4	285.75	10-ø20.6	223.2	1x45°	0	5150
BW22114	6.6	14	61.6	203.2	8-ø16.7	152.7	90°	8	-
BW22122	7	14	55.3	285	8-ø32	221	SR22	114	-
BW22139	6.6	14	61.5	203.2	8-ø17.5	152.4	90°	13	5150
BW22140	6.6	14	60.4	285.75	10-ø20.6	223.2	1x45°	13	5150

22.5 x 14.0

STEEL WHEELS

Reccomended tyre size(s): 425/65R22.5 | 435/50R22.5 | 445/50R22.5 | 445/65R22.5 | 445/75R22.5 | 455/45R22.5

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2247	7	14	54.8	335	10-ø26	281	1x45°	0	5600
BW2247A	7	14	52.22	335	10-ø26	281	1x45°	120	5600
BW2247C	7	14	54.8	335	10-ø26	281	1x45°	0	5600
BW2247D	7	16	57.2	335	10-ø26	281	1x45°	0	5600
BW2247E	7	14	54.8	335	10-ø26	281	1x45°	90	5600
BW2248	7	14	54.76	335	10-ø27	281	SR18	0	5600
BW2248A	7	14	52.17	335	10-ø27	281	SR18	120	5600
BW2248B	7	14	54.76	335	10-ø27	281	SR18	0	5600
BW2248C	7	12	50	335	10-ø27	281	SR18	0	5600
BW2248D	7	12	-	335	10-ø27	281	1x45°	0	-
BW2285	7	13	-	275	8-ø26	221	1x45°	0	5600
BW2285A	7	12	-	275	8-ø26	221	SR18	0	5600
BW2273	7	14	54.11	335	10-ø27	281	SR18	180	5600
BW2287	7	14	-	275	8-ø21.5	221	one side SR16	0	5600
BW2293C	7	16	58.44	285.75	10-ø26	220	1x45°	0	5600

22.5 x 14.0

STEEL WHEELS

Reference No.	Rim (mm)	Disc (mm)	Wheel Weight (kg)	P.C.D (mm)	Bolt Holes	Centre Hole (mm)	Bolt Type	Offset (mm)	Capacity (kg)
BW2293D	7	14	55.7	285.75	10-ø26	220	1x45°	0	5600
BW22146	7	14	54.8	335	10-ø26	281	SR18	0	5600



WHO WE ARE

TIA GROUP

With 25 years of industry expertise, the TIA Group proudly supports both the after-market and OEM sectors through our three specialised divisions: tyres, wheels and agricultural.

Our divisions serve a wide spectrum of the industry, from commercial to industrial, collaborating with some of the most respected names in transport.

TIA GROUP TIA WHEELS TIA TYRES TIA AGRI

WHOLESALE SERVICES

We supply tyres directly from our warehouse, letting you order any quantity with fast delivery, competitive pricing, and the support of our expert customer service team. Our **Super Wholesale** service delivers container shipments of budget tyres directly from the factory to your door, with access to discounted warehouse backup stock for added convenience.

OUR DIVISIONS

TIA GROUP

TIA TYRES | TBR & PCR TYRE SPECIALISTS

Since 1999, TIA Tyres has been a leading force in tyre wholesale, delivering a broad range of passenger car, high-performance, 4x4, van, truck and bus tyres.

Our TBR division works closely with brands across every tier of the market from premium names such as Bridgestone and Continental, to mid-range leaders like Yokohama and CEAT, all the way through to dependable budget options including Torque.

TORQUE CEAT YOKOHAMA

Our PCR team specialises in the wholesale distribution of car and van tyres, supporting customers from national depots to local garages across the country, focusing on a variety of budget to mid-range brands. Orders ship twice daily, ensuring the quickest possible delivery, straight to your door.

TIA AGRI | CONSTRUCTION & AGRI SPECIALISTS

Launched in 2022, TIA Agri is the newest addition to the TIA Group and has quickly established itself as an industry leader of agricultural and construction tyres.

Our portfolio brings together a diverse mix of leading brands, each offering proven solutions across both agricultural and construction applications.

ALLIANCE GOODYEAR FARM TIRES JCB SITEMASTER

Backed by a seasoned team with deep knowledge of the sector, we go beyond simply supplying tyres. We pride ourselves on our hands-on approach, including farm visits and on-site tyre optimisation, ensuring every solution we provide is practical and reliable.

Your partner in wheels,
from production to distribution

Halesfield 13, Telford, TF7 4PL
sales@tiawheels.co.uk
+44 01952 327676